Centro Tessile Serico

Centro Tessile Serico Spa consortile
via Castelnuovo, 3 22100 Como, Italia
P.IVA - C.F. 02361270137
Capitale sociale 541.666,78 i.v.
mailbox@textilecomo.com
www.textilecomo.com

Servizio Clienti Laboratorio +39 031 3312120
Segreteria Laboratorio +39 031 3312121-170-171
Segreteria di Direzione
e Amministrazione +39 031 3312102
Contabilità +39 031 3312154
Area Certificazione +39 031 3312133
Marchio Seri.co +39 031 3312132
Fax +39 031 3312180

Report nr. **1501655-002**

TEST	M.U.	RESULTS
14323-ar PROPENSITY TO SURFACE PILLING (Martindale)		-
Method: UNI EN ISO 12945-2/02		
Instrument: Abrasion Tester Martindale J.Heal - NU - 406		
Number of observers: 02		
EXPLANATORY NOTE OF THE RESULTS Grade 5: no change Grade 4: slight surface fuzzing and/or partially formed pills Grade 3: moderate surface fuzzing and/or moderate pilling. Pills of varying size and density partially covering the specimen surface Grade 2: distinct surface fuzzing and/or distinct pilling. Pills of varying size and density covering a large proportion of the specimens surface. Grade 1: dense surface fuzzing and/or severe pilling. Pills of varying size and density covering the whole of the specimen surface.		
Date of test:		09-03-2015
Pretreatment carried out		NO ONE
Change at 500 revs.	grade	4-5
Change at 1000 revs.	grade	4-5
Change at 2000 revs.	grade	4-5
Change at 5000 revs.	grade	4
The final grade above refers to pilling and fuzzing.		
Number of specimens:	nr.	3
Abradent:		Abradant wool
Load applied:	g	415
Deviation from procedure		-

14063 RESISTANCE TO ABRASION (Martindale) - DETERMINATION OF SPECIMEN BREAKDOWN		
Method: UNI EN ISO 12947-2:2000 + EC 1-2010		
Instrument: Abrasion Tester Martindale J.Heal - 103		
SPECIMEN BREAKDOWN Specimen breakdown is reached when: - in woven fabric, when two separate threads are completely broken; - in knitted fabric, when one thread is broken causing a hole; - in pile fabric, when the pile is fully worn off; - in nonwoven fabric, when the first hole is of a diameter at least equal to 0,5 mm.		
Date of test:		13/3/2015
Pretreatment carried out		No one
First specimen: cycles to end point	cycles	>50000
Second specimen: cycles to end point	cycles	>50000
Third specimen: cycles to end point	cycles	>50000
Average	cycles	>50000
Confidence limits		-
Load applied	kPa	12
Change in colour at the end point (when stated)	grade	N.D.
Pilling occured	cycles	-
Deviation from procedure		-
Enclosed:	nr.	1